

## Stator (Stick) Sensors Cross Reference List

## Standard vs Old Ex Certified vs New Ex Certified

			OLD ATEX/IECEx/CSA Certified		New ATEX/IECEx/CSAc-us Certified*	
Туре	Body Thickness	Standard Model Numbers (non-Ex)	Wire Wound Element	Thin-film Element	Wire Wound Element(s)	Thin-film Element(s)
RTD	.030"	S1220, S1240, S1420, S8010, S100305, S100415	n/a	n/a	n/a	n/a
	.050"	S7401, S8014	n/a	n/a	S115, S125	S135, S145
	.078"/.079"	S13, S15, S18, S8012, S11016	S100050	S200050	S110, S120	S130, S140
	.098"		S100051	S200051	S111, S121	S131, S141
	.118"		S100052	S200052	S112, S122	S132, S142
	.125"	S8016	n/a	n/a	n/a	n/a
	.138"		S100053	S200053	S113, S123	S133, S143
	.157"		S100054	S200054	S114, S124	S134, S144
	.069"		S100055	S200055	S116	S136

<sup>\*</sup>CSAc-us certification for S1xx models covers usage for both Canada and United States.

Yellow highlighted cells are models that will be phased out and replaced by new S1xx models in last two columns.